

(12) United States Patent

Watanabe et al.

US 6,693,774 B2 (10) Patent No.:

(45) Date of Patent: Feb. 17, 2004

(54) MAGNETORESISTIVE SENSOR AND MAGNETIC STORAGE APPARATUS

(75) Inventors: Katsuro Watanabe, Odawara (JP);

Hiromasa Takahashi, Hachioji (JP); Nobuo Yoshida, Odawara (JP); Takashi Kawabe, Hitachi (JP); Kazuhiro

Nakamoto, Tokyo (JP)

Assignee: Hitachi, Ltd., Tokyo (JP)

Subject to any disclaimer, the term of this (*) Notice: patent is extended or adjusted under 35

(JP) 2000-073925

U.S.C. 154(b) by 246 days.

(21) Appl. No.: 09/803,032

(22)Filed: Mar. 12, 2001

(65)**Prior Publication Data**

US 2001/0028538 A1 Oct. 11, 2001

(30)	Foreign	Application	Priority	Data
------	---------	-------------	-----------------	------

(51)	Int. Cl. ⁷	G11B 5/127 ; G11B 5/39
(52)	U.S. Cl	
2	*** ** ** *	

Field of Search 360/319, 320, 360/317, 324, 324.1, 324.2, 323, 313, 110

(56)References Cited

U.S. PATENT DOCUMENTS

5,206,590 A 4/1993 Dieny et al. 324/252

	5,568,335	A	*	10/1996	Fontana et al 360/320
	5,936,810	Α		8/1999	Nakamoto et al 360/324.1
	6,292,334	B 1	*	9/2001	Koike et al 360/319
	6,452,761	B1	*	9/2002	Carey et al 360/320
20	02/0015267	A 1	*	2/2002	Sato 360/320
20	02/0027753	A 1	*	3/2002	Ishiwata et al 360/324.2

FOREIGN PATENT DOCUMENTS

JP	4-358310	12/1992
JP	5-266437	10/1993
JP	9-282618	10/1997

^{*} cited by examiner

Primary Examiner—Julie Anne Watko (74) Attorney, Agent, or Firm-Antonelli, Terry, Stout & Kraus, LLP

(57)**ABSTRACT**

A magnetoresistive sensor which, despite a narrow reproducing shield gap, affords high resolution and high reproducing output because of its structure and is able to minimize the amount of sense current leaking into the shield layer through the gap layer. A magnetic storage apparatus suitable for high-density recording is provided with a magnetic head having said magnetoresistive sensor. The structure is characterized in that at least either of the lower shield layer or upper shield layer is partly or entirely a magnetic layer which is a composite film composed of ferromagnetic metal and oxide, and an insulation protective film is arranged between the electrode film or longitudinal bias film and the magnetic film which is a composite film composed of ferromagnetic metal and oxide.

14 Claims, 12 Drawing Sheets

